



NAŚWIETLACZE LED / LED FLOODLIGHTS

LED MHNC 20W




PREMIUM



- projektor oświetleniowy z mikrofalowym czujnikiem ruchu o trzech zakresach regulacji: czas działania, natężenie światła i zasięg detekcji,
- regulacja za pomocą pilota,
- czas działania: 10 sek, 30 sek, 1 min, 5 min, 8 min, 10 min,
- natężenie światła: wyłączony lub 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- zasięg detekcji: max. 10 m oraz do 5 m i do 8 m,
- kąt detekcji: 120 stopni,
- kąt rozsyłu światła: 120 stopni,
- optymalna wysokość do montażu: 1,8 – 2,5 m,
- nie można wymieniać lamp w oprawie.

- lighting projector with microwave motion sensor of three ranges of adjustment: working time, light intensity and detection range,
- adjustment by a remote,
- working time: 10 sec, 30 sec, 1 min, 5 min, 8 min, 10 min,
- light intensity: off or 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- detection range: max. 10 m and up to 5 m and to 8 m,
- detection angle: 120 degrees,
- beam angle: 120 degrees,
- optimal installation height: 1,8 – 2,5 m,
- lamps inside are unchangeable.



MODEL	INDEKS	POBÓR MOCY [W]	BARWA ŚWIATŁA	STRUMIEŃ ŚWIETLNY [lm]	WAGA NETTO [kg]	PAKOWANIE [szt.]	KOD EAN
MODEL	INDEX	POWER [W]	LIGHT COLOR	LUMINOUS FLUX [lm]	NET WEIGHT [kg]	PACKING [pcs.]	BARCODE
LED MHNC 20W CB	KFNLC20CB2	20	CIEPŁOBIAŁA WARM WHITE	1600	0,30	30	5902201303698
LED MHNC 20W NB	KFNLC20NB2	20	NEUTRALNA BIAŁA NEUTRAL WHITE	1600	0,30	30	5902201303704
LED MHNC 20W ZB	KFNLC20ZB2	20	ZIMNOBIAŁA COOL WHITE	1600	0,30	30	5902201303711

230V~

50Hz



IP65



LED



3000K



4000K



6500K



25 000

cosφ

Pf≥0,50

Ra

≥80



20 000



-25°C
↕
40°C

