



PROFESSIONAL LINE

OSPRZĘT LED / LED EQUIPMENT

ZASILACZ DALI 44W

/ DALI DRIVER 44W



- możliwość ściemniania: 0-10V, DALI, PUSH,
- możliwość regulacji prądu wyjściowego w zakresie 550-1050 mA (co 50 mA),
- napięcie wejściowe 220-240V AC (198-264V AC),
- napięcie wyjściowe 25-42V DC,
- temperatura składowania -30-80°C,
- certyfikaty: ENEC, CE,
- standard DALI 2.0,
- zabezpieczenie przepięciowe: L-N 1 kV,
- kompatybilny z oprawami LED CAPRI, LED NELIO, LED CAMARO, LED ORIO i LED NEXEYE 30W.

- dimming: 0-10V, DALI, PUSH,
- output current can be adjusted in a range 550-1050 mA (every 50 mA),
- input voltage: 220-240V AC (198-264V AC),
- output voltage: 25-42V DC,
- can be stored in a temperature: -30-80°C,
- certificates: ENEC, CE,
- DALI 2.0,
- overvoltage protection: L-N 1KV,
- compatible with fixtures LED CAPRI, LED NELIO, LED CAMARO, LED ORIO and LED NEXEYE 30W.

MODEL	INDEKS	MAX MOC [W]	WYMIARY [mm]	WAGA NETTO [kg]	PAKOWANIE [szt.]	KOD EAN
MODEL	INDEX	MAX POWER [W]	SIZE [mm]	NET WEIGHT [kg]	PACKING [pcs.]	BARCODE
ZASILACZ DALI 44W	KFCPZD36	44	107X70X29	0,17	1	5902201364606

cosφ
DF≥0,90-30°C
↑↓
50°C