

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kobi

Supplier's address: Kobi LIGHT, Boya Żeleńskiego 2 35-105 Rzeszów Polska

Model identifier: LED VALLE 4,2W 3000K

Type of light source:

| | | | |
|---|-----|---------------------------------|-----|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | - | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | Nie |
| Colour-tuneable light source: | Nie | Envelope: | - |
| High luminance light source: | Nie | | |
| Anti-glare shield: | Nie | Dimmable: | No |

Product parameters

| Parameter | Value | Parameter | Value |
|--|--------------------------|--|------------------------|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 4 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 253 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P_{on}), expressed in W | 4,2 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer dimensions without | Height | Spectral power distribution in the | See image in last page |
| | Width | | |
| | Depth | | |

| | | | | |
|---|------|--|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | | | range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | |
| | | Chromaticity coordinates (x and y) | 0,440 0,403 | |
| Parameters for directional light sources: | | | | |
| Peak luminous intensity (cd) | - | Beam angle in degrees, or the range of beam angles that can be set | 38 | |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | 1 | Survival factor | 0,90 | |
| the lumen maintenance factor | 0,93 | | | |
| Parameters for LED and OLED mains light sources: | | | | |
| displacement factor (cos ϕ_1) | 0,50 | Colour consistency in McAdam ellipses | 6 | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W) | - | |
| Flicker metric (Pst LM) | - | Stroboscopic effect metric (SVM) | - | |

(a) '-': not applicable;

(b) '-': not applicable;

