



PROFESSIONAL LINE


OPRAWY LED / LED FIXTURES

HPL 2 PRO 120W / 90°



- oprawa z wbudowanymi diodami LED z przestoną pryzmatyczną,
- obudowa wykonana z aluminium, przestona z poliwęglanu PC,
- typy montażu: zwieszany / górny z regulacją kąta / boczny z regulacją kąta,
- oprawa zawiera źródła światła w klasie energetycznej C,
- możliwość wymiany źródła światła LED jedynie przez wykwalifikowany personel.

- fixture with built-in LED diodes and prismatic cover,
- fixture's body made of aluminium, tempered PC cover,
- installation type: suspended / upper with angle adjustment / lateral with angle adjustment,
- fixture includes built-in light sources in energy class: C,
- LED light sources can be replaced only by qualified personel.



MODEL	INDEKS	POBÓR MOCY [W]	KĄT ROZSYŁU ŚWIATŁA	TEMPERATURA BARWOWA (K)	STRUMIEŃ ŚWIETLNY [lm]	WAGA NETTO [kg]	PAKOWANIE [szt.]	KOD EAN
MODEL	INDEX	POWER [W]	BEAM ANGLE	COLOR TEMPERATURE [K]	LUMINOUS FLUX [lm]	NET WEIGHT [kg]	PACKING [pcs.]	BARCODE
HPL 2 PRO 120W	02NSHL2129P	120	90	4000	16164	6,85	1	5902846010371
HPL 2 PRO 120W	02NSHL21295P	120	90	5000	16164	6,85	1	5902846012290

